

QSX15-G13



Emissions Compliance:

EPA Tier 3
EU Stage IIIA

> Specification sheet



Our energy working for you.™

Description

The QSX15 engine is designed to meet the U.S. Environmental Protection Agency (EPA) Tier 3 and European Union (EU) Stage IIIA genset emission standards. It uses in-cylinder technology, a simple and cost-effective solution that maintains the proven performance and durability of the QSX15, while operating cleanly and efficiently. Designed with proven heavy-duty components for dependability, the QSX15 engine is capable of delivering optimum performance at every rpm.

The 15 litre, six-cylinder QSX15 engine is ideally suited to both open and containerised applications in static or portable genset equipment. It can be matched to meet specific duty cycle and operating conditions of any genset.



This engine has been built to comply with CE certification.



This engine has been designed in facilities certified to ISO9001 and manufactured in facilities certified to ISO9001 or ISO9002.

Features

Cummins Extra High Pressure Injection (XPI) Fuel System – Most capable common-rail fuel system utilized on a heavy-duty engine, enabling faster, smoother power delivery with lower fuel consumption.

Turbocharger System – A new electronic variable geometry turbocharger (VGT) is used, which is able to continuously vary airflow boost and manage the EGR.

Exhaust Gas Recirculation (EGR) System – Proven cooled EGR system that reduces nitrogen oxide (NOx) emissions.

Crankcase Breaker – Utilizes a “dripless” crankcase breather system.

Electronic Control System – Provides faster processing power and increased memory capability while allowing seamless electronic interface to other systems.

Service and Support - G-Drive products are backed by an uncompromising level of technical support and after sales service, delivered through a world class service network.

1500 rpm (50 Hz Ratings)

Gross Engine Output			Typical Generator Set Output					
Standby	Prime	Base	Standby (ESP)		Prime (PRP)		Base (COP)	
kWm/BHP			kWe	kVA	kWe	kVA	kWe	kVA
462/619	418/561	377/505	400	500	364	455	321	401

1800 rpm (60 Hz Ratings)

Gross Engine Output			Typical Generator Set Output					
Standby	Prime	Base	Standby (ESP)		Prime (PRP)		Base (COP)	
kWm/BHP			kWe	kVA	kWe	kVA	kWe	kVA
521/699	472/633	425/570	450	563	409	511	365	456

Our energy working for you.™

www.cumminsgdrive.com

©2011 | Cummins G-Drive Engines | Specifications Subject to Change Without Notice | Cummins is a registered trademarks of Cummins Inc. S-1650 (12/11)



General Engine Data

Type	4 Cycle, In-line, Turbo Charged, Air Cooled
Bore mm	137 mm (5.39 in.)
Stroke mm	169 mm (6.65 in.)
Displacement Litre	14.9 litre (912 in. ³)
Cylinder Block	Cast iron, 6 cylinder
Battery Charging Alternator	35 amps
Starting Voltage	24 volt
Fuel System	XPI
Fuel Filter	Primary spin-on fuel filter – OEM Fitted Secondary fuel filter with water separator
Lube Oil Filter Type(s)	Spin-on full flow filter
Lube Oil Capacity (l)	91.0
Flywheel Dimensions	SAE1

Ratings Definitions

Emergency Standby Power (ESP):

Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.

Limited-Time Running Power (LTP):

Applicable for supplying power to a constant electrical load for limited hours. Limited-Time Running Power (LTP) is in accordance with ISO 8528.

Prime Power (PRP):

Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.

Base Load (Continuous) Power (COP):

Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) in accordance with ISO 8528, ISO 3046, AS 2789, DIN6271 and BS 5514.

Engine Weight & Dimensions

Length	Width	Height	Weight (dry)
mm	mm	mm	kg
1528	1257	1107	1436

Fuel Consumption 1500 (50 Hz)

%	kWm	BHP	L/ph	US gal/ph
Standby Power				
100	462	619	108	28.5
Prime Power				
100	418	561	98	25.8
75	314	421	74	19.6
50	210	281	50	13.1
25	104	140	27	7.2
Continuous Power				
100	377	505	89	23.4

Fuel Consumption 1800 (60 Hz)

%	kWm	BHP	L/ph	US gal/ph
Standby Power				
100	521	699	130	34.5
Prime Power				
100	472	633	117	30.9
75	354	475	85	22.4
50	236	316	58	15.3
25	118	158	32	8.6
Continuous Power				
100	425	570	104	27.4

Cummins G-Drive Engines

Asia Pacific

10 Toh Guan Road
#07-01
TT International Tradepark
Singapore 608838
Phone 65 6417 2388
Fax 65 6417 2399

Europe, CIS, Middle East and Africa

Manston Park Columbus Ave
Manston Ramsgate
Kent CT12 5BF, UK
Phone 44 1843 255000
Fax 44 1843 255902

Latin America

Rua Jati, 310, Cumbica
Guarulhos, SP 07180-900
Brazil
Phone 55 11 2186 4552
Fax 55 11 2186 4729

Mexico

Cummins S. de R.L. de C.V.
Eje 122 No. 200 Zona Industrial
San Luis Potosí, S.L.P. 78090
Mexico
Phone 52 444 870 6700
Fax 52 444 870 6811

North America

1400 73rd Avenue N.E.
Minneapolis, MN 55432
USA
Phone 1 763 574 5000
USA Toll-free 1 877 769 7669
Fax 1 763 574 5298

Our energy working for you.™

www.cumminsgdrive.com

©2011 | Cummins G-Drive Engines | Specifications Subject to Change Without Notice | Cummins is a registered trademarks of Cummins Inc.
S-1650 (12/11)

